

PROJECT ASSURE
DIAMOND VERIFICATION INSTRUMENT STANDARD
TEST RESULTS

Assessment Report for: MindronTech TruSure Median



Prepared For: Luc Auer
Natural Diamond Council Belgium VOF
Hoveniersstraat 22
2018 Antwerpen

Assessment Date: February 23 – March 13, 2026


Testing ID Number: Category 1-6

Report Date: 31/03/2025

Approved by:

Didier Backaert
Lab Manager

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients' right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as "Passed," do not indicate or certify that the product is safe for commercial or consumer use.

	MidronTech TruSure Median		
	Date:	31/03/2026	Testing ID:

DIAMOND VERIFICATION INSTRUMENT

Manufacturer's Name: MindronTech
Instrument Model: TruSure Median
Serial Number: n/a
Software Version: 1.0.10

Lab Manager: Didier Backaert
Analyst/Operator : Nathan

Manufacturer-stated diamond verification instrument description and features:

The TruSure Median by MindronTech is a portable desktop diamond verification instrument designed to detect Natural Diamonds, Synthetic Diamonds, and Diamond Simulants. The device features a large scanning area of 225mm x 125mm to accommodate testing of many loose stones at a time, and large jewelry pieces. It has the following features and benefits:

- Capable of identifying loose and mounted natural diamonds, CVD and HPHT synthetic diamonds in D to K color range.
- Capable of identifying diamond simulants such as cubic zirconia, sapphire, glass and moissanite.
- Provides up to 22x zoom with high-resolution imaging.
- Features fluorescence and phosphorescence detection.
- Supports auto and manual focus.
- Capable of testing stones as small as 0.002ct
- Capable of fast scanning (25 seconds per scan).

INSTRUMENT PERFORMANCE ASSESSMENT

ASSESSMENT CRITERIA

The ASSURE testing methodology and performance metrics are dependent on the operational capabilities of the diamond verification instrument being tested. These are defined by the following three categories:

Category 1- Screen diamonds from synthetic diamonds. This category of device is intended for discrimination of diamonds from synthetic diamonds. It cannot distinguish diamonds from diamond simulants and therefore requires stones to be pre-screened to ensure no simulants are introduced into the device.

Category 2 – Screen diamonds from synthetic diamonds and diamond simulants. This category of device is intended for discrimination of diamonds from synthetic diamonds and diamond simulants. This device cannot distinguish synthetic diamonds from diamond simulants.

Category 3 – Screen diamond from synthetic diamonds from diamond simulants. This category of device is intended for discrimination of diamonds, synthetic diamonds and diamond simulants from each other. This device can distinguish synthetic diamonds from diamond simulants.

Instrument performance for classifying the different kinds of stones was assessed against:

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients' right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as "Passed," do not indicate or certify that the product is safe for commercial or consumer use.




- Diamond Verification Instrument Standard Part 1 – Diamond Verification Instrument for Screening Diamonds from Synthetic Diamonds (18 03 2024)
- Diamond Verification Instrument Standard Part 2 – Diamond Verification Instrument for Screening Diamonds from Synthetic Diamonds and Diamond Simulants (18 03 2024)
- Diamond Verification Instrument Standard Part 3 – Diamond Verification Instrument for Screening Diamonds, Synthetic Diamonds, and Diamond Simulants (18 03 2024)

as referenced in sections 7.3 and 7.4 of the Diamond Verification Instrument Standard – General Requirements for Evaluation Diamond Verification Instruments (18 03 2024). Any deviations from the Standard are noted below:

DEFINITIONS:

Diamond Accuracy	<i>Diamond test stones correctly classified as Diamond.</i>
Synthetic Diamond Accuracy	<i>Synthetic Diamond test stones correctly classified as Synthetic Diamond.</i>
Diamond Simulant Accuracy	<i>Diamond Simulant test stones correctly classified as Diamond Simulant.</i>
Diamond Referral Rate	<i>Diamond test stones classified as Referral.</i>
Synthetic Diamond Referral Rate	<i>Synthetic diamond test stones classified as Referral</i>
Simulant Referral Rate	<i>Diamond simulant test stones classified as Referral</i>
Diamond False Positive Rate	<i>Synthetic Diamond / Diamond Simulant test stones incorrectly classified as Diamond.</i>
Synthetic Diamond False Positive Rate	<i>Diamond / Diamond Simulant test stones incorrectly classified as Synthetic Diamond.</i>
Diamond Simulant False Positive Rate	<i>Diamond / Synthetic Diamond test stones incorrectly classified as Diamond Simulants.</i>
Diamond False Negative Rate	<i>Diamond test stones incorrectly classified as Synthetic Diamonds or Diamond simulants.</i>
Synthetic Diamond False Negative Rate	<i>Synthetic Diamond test stones incorrectly classified as Diamonds or Diamond simulants</i>
Diamond Simulant False Negative Rate	<i>Diamond Simulant test stones incorrectly classified as Diamonds or Synthetic Diamonds</i>
Testing Speed	<i>The average speed at which the diamond verification instrument evaluates the stones in the PRIMARY loose sample set, including set-up time (if any)</i>
Operating Speed	<i>For auto-loading diamond verification instruments only, the average speed at which stones are evaluated once the instrument achieves a steady-state. does not include set-up time.</i>

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients' right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as "Passed," do not indicate or certify that the product is safe for commercial or consumer use.

 Bonas Group DIAMONDS & GEMSTONES	MidronTech TruSure Median		
	Date: 31/03/2026	Testing ID:	Category 1-6

TEST STONE SETS USED FOR EVALUATION

Loose, Polished Stone Test Sets	Diamond	Synthetic Diamond	Diamond Simulant
Primary Sample Set (>2.0 mm, D-J color)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Supplementary Smalls Sample Set (1.0-2.0 mm, D-J color)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Supplementary Ultra Smalls Sample Set (0.5-1.0mm D-J color)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Mounted, Polished Stone Test Sets	Diamond	Synthetic Diamond	Diamond Simulant
Primary Sample Set (>2.0 mm, D-J color)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Supplementary Smalls Sample Set (1.0-2.0 mm, D-J color)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Notes: MindronTech claims the TruSure Median is capable of testing ultra small sized diamonds, however this was not tested by ASSURE since the Ultra Smalls sample set is only used for devices with fully automated feed.

CLEANING PROCEDURE OF STONES PRIOR TO TESTING

Test stones sets are cleaned in an ultrasonic bath of isopropanol for 2 minutes and dried prior to testing to reduce grease and electrostatic charge, as per Section 8 of ASSURE Standard.

LABORATORY CONDITIONS AT TIME OF ASSESSMENT

Condition	Requirement	Actual
Temperature (°C)	18 to 25°C	23 °C
Humidity (%)	50 to 65%	57 %

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients' right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as "Passed," do not indicate or certify that the product is safe for commercial or consumer use.



RESULTS OF INSTRUMENT PERFORMANCE ASSESSMENT – LOOSE STONES

Performance Metric	Primary ^[1]	Uncertainty ^[2]	Smalls ^[3]	Uncertainty ^[2]	Ultra-Smalls ^[5]
Diamond accuracy (%)	95.7	1.1	94.9	1.4	n/a
Synthetic diamond accuracy (%)	71.7	1.3	97.0	1.3	
Diamond Simulant accuracy (%)	74.0	0.9	n/a ^[4]	n/a	
Diamond referral rate (%)	4.3	1.1	5.1	1.4	
Synthetic diamond referral rate (%)	16.3	1.3	3.0	1.3	
Diamond Simulant referral rate (%)	26.0	0.9	0.0	0.0	
Diamond false positive rate (%)	0.0	0.0	0.0	0.0	
Synthetic Diamond false positive rate (%)	0.0	0.0	0.0	0.0	
Diamond Simulant false positive rate (%)	2.7	0.9	n/a ^[4]	n/a	
Diamond false negative rate (%)	0.0	1.3	0.0	0.0	
Synthetic diamond false negative rate (%)	12.0	0.0	0.0	0.0	
Diamond Simulant false negative rate (%)	0.0	0.0	n/a	n/a	


- Notes:
- ^[1] Primary set comprised of round brilliant loose stones with diameters of >2.0 mm D-J color.
 - ^[2] Uncertainty is expressed as absolute +/- range and reflects the consistency of the instrument’s classification of stones for each of the three trials performed with the ASSURE sample.
 - ^[3] Smalls set comprised of round brilliant loose stones with diameters of 1.0–2.0 mm D-J color.
 - ^[4] Simulants not included in Smalls sample set
 - ^[5] Ultra-Smalls (<1.0mm diameter) is only included for devices with fully automated feed.

RESULTS OF INSTRUMENT PERFORMANCE ASSESSMENT – MOUNTED STONES

Performance metric	Primary ^[1]	Smalls ^[2]
Diamond accuracy (%)	86.4	83.0
Synthetic diamond accuracy (%) ^[3]	85.4	71.4
Diamond Simulant accuracy (%)	45.5	n/a
Diamond referral rate (%) ^[3]	11.8	8.5
Synthetic diamond referral rate (%) ^[3]	12.2	0.0
Diamond Simulant referral rate (%)	36.4	n/a
Diamond false positive rate (%)	1.9	0.0
Synthetic diamond false positive rate (%) ^[3]	2.2	4.3
Diamond Simulant false positive rate (%)	0.4	5.6
Diamond false negative rate (%)	1.8	8.5
Synthetic diamond false negative rate (%)	2.4	14.3
Diamond Simulant diamond false negative rate (%)	18.2	n/a

- Notes:
- ^[1] Primary sample set has stones with diameters of >2.0 mm D-J color with open-back setting.
 - ^[2] Smalls sample set has stones from 1.0 – 2.0 mm in diameter D-J color with closed-back setting.

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients’ right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as “Passed,” do not indicate or certify that the product is safe for commercial or consumer use.

 Bonas Group DIAMONDS & GEMSTONES	MidronTech TruSure Median		
	Date: 31/03/2026	Testing ID:	Category 1-6

INSTRUMENT TESTING SPEED ASSESSMENT

Testing Speed approximates the usage turnaround time that could be expected by a novice user of the diamond verification instrument and is determined by the time required to evaluate the performance of the diamond verification instrument on the Primary Loose stone test set:

- Testing Speed accounts for the time directly associated with stone assessment including loading stones, programming any applicable instrument measurement parameters, analyzing the stones, and segregating the analyzed stones into respective instrument classified groups.
- Testing Speed does not include the time to initially warm-up the diamond verification instrument (if applicable) nor the time to separate diamonds from synthetic diamonds for each of the instrument classified groups of analyzed stones.
- Testing Speed does not include time associated with interruptions to the testing process.

Diamond verification instruments that continuously load and analyze stones (i.e., autoloading diamond verification instruments) shall also be assessed for a steady-state Instrument Operating Speed.

Testing speed, and instrument operating speed if applicable, are measured in triplicate. The mean value is reported in the Speed Test Results table below. The uncertainty reflects the absolute +/- range of the results measured over the three trials.

SPEED TEST RESULTS (PRIMARY LOOSE SAMPLE)

Category	Stones per hour	Uncertainty
Testing Speed (all devices)	451	10
Operating Speed (auto-loading devices)	N/A	N/A

Notes:

ADDITIONAL FINDINGS

- The Trusure Median has semi-automatic interpretation, with stones color-coded by the device to indicate category. However, some stones require manual interpretation as per user manual.
- Trusure recommends that expert gemologists may be required for final verification, especially in complex cases.
- User should tap “Check for Updates” prior to using device to ensure latest software version is installed. Software version 1.0.10 was used at time of testing for ASSURE.

***** End of Report *****

LETTERS & REPORTS: Bonas reports are issued for the exclusive use of the clients to whom they are addressed. No quotations from reports or use of the Bonas name is permitted except as expressly authorized in writing. Letters and reports apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. The liability of Bonas with respect to services rendered shall be limited to the amount of consideration paid for such service and not include any consequential damages. This report or certificate does not relieve sellers/suppliers from their contractual responsibility with regard to the quality/quantity of this delivery, nor does it prejudice clients' right to claim towards sellers/suppliers for compensation for any apparent and/or hidden defects not detected during our random inspection or testing. Bonas has not performed a complete analysis of the product. The results contained in this report indicate that the product has passed or failed the specific tests only. These test results, even if rated as "Passed," do not indicate or certify that the product is safe for commercial or consumer use.